



Powertrain		
	Standard	Optional
Engine	Cummins QSB 6.7L 173 HP	ISB 6.7L 200 HP [DOT]
Transmission	Allison RD 3500	
Gears	1-2-3-4-5-6	Creep -1-2-3-4-5-6 w/ EZ Trac
Fuel Tank	50 Gallons	

Chassis		
	Standard	Optional
Front Axle	Hendrickson STEERTEK NXT 14,600 LB	EZ Trac Hydraulic AWD
Suspension	Hendrickson AIRTEK	
Brake	16.5 x 5 s-cam	
Steering	Hydraulic	TRW -TAS85 [DOT]
Rear Axle	PRC785 Axletech (30,000 LB) 10.5:1 Ratio	Differential Lock
Suspension	Hendrickson 30,000 LB HD	
Brake	16.5 x 7 s-cam	
Fifth Wheel	SF Holland FW35 - 70,000 lbs	
Front Tires	11R22.5 Radials	425/65R22.5
Rear Tires	11R22.5 Radials	445/65R22.5
Wheel	22.5 Steel Hub Piloted, 335mm BC	

Cab & Trim		
	Standard	Optional
Structure	Steel, Structural Tube	
Isolation	4 point, fulcrum-focused mounting	
Tilt	Cam Gas Spring	
Entry	Rear Sliding Door, 24" x 72"	
Mirrors	Dual West Coast	Powered/Heated/Convex
HVAC	45,000 BTU W/ AC	
Insulation	Thermal and Noise	
Seat	Sears, air suspended w/ 3 point seat belt	
Fenders	Rear Fenders w/ Mud flaps	

Hydraulic	
Standard	
Flow	41.6 GPM @ 2500 RPM
Tank	2.5 Gallon

Static Dimensions		[in]
A	Overall Length	186
B	Wheelbase	116
C	Clearance Width	99
D	Overall Height	134
E	Overall Width	115
F	Ground Clearance	12
G	Approach Angle	40°
H	Fifth Wheel Height Low Position	44
I	Fifth Wheel Height Upper Position	62
J	Fifth Wheel to center line of rear axle	10
K	Trailer Clearance	80
L	Front Tire to Front Bumper	42
M	Rear Tire to Rear Bumper	28
N	Cab Width	65

Electrical		
	Standard	Optional
System	12V	
Alternator	130 Amp	
Battery	2 x 950 CCA	
Headlights	LED	
Stop/Turn/ Tail	LED	
Warning/Hazards	LED	
Work lamps	LED	
Beacon	LED	

Air	
Standard	
Compressor	Wabco 18.7 CFM
Tank	4100in ³